

Features

TruVision 6 Port POE Switch

- 4*10/100Mbps RJ45 PoE port
- 2*10/100Mbps RJ45 Uplink port
- The whole power is up to 72W(52V 1.5A).
- The max. power is 30W for single port
- 250m Distance
- Support IEEE802.3AF/AT
- All port supported by MDI/MDIX auto flip and self negotiation
- Supply 4 10/100Mbps adaptive high speed forwarding data packet non-lost port.
- Support IEEE802.3x flow control for Full-duplex mode and backpressure for Half-duplex mode.



Specifications

Model	PSE-6004 / TVS-NT-42POE
Product	6 Port 250m POE Switch (Internal)
POE Port	1 to 4 support IEEE802.3AF/AT Standard
Output Power	15.4W/30W IEEE802.3af/at
Power Pin	Both 1/2+, 3/6- and 4/5+7/8-
Whole Power	≤78W (52V 1.5A)
POE Protocol	IEEE 802.3af/IEEE 802.3at
POE Type/Power Distance	End-span/ 250m
Network Standard	IEEE 802.3、IEEE802.3u、802.3x、802.3af/at
Network Medium	10/100BASE-TX:5 class and above non shielded twisted pair
Data Distance/Switch Capability	250m/ 1Gbps
Forwarding Mode	Store and forward
Forwarding Rate	10BASE-T:14880PPS/port ,100BASE-tx : 14800pps/port
MAC Address	MAC address table 1K
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging ,IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
LED Indicator	LINK/ACT.100Mbps;POE Status Indicator; Power indicator;Extender
Working Environment	Working temperature : -10°-- 55°C
Size	136×66×32(L*W*H)mm



MAKE LIFE SAFE & SMART

www.tvssecurity.com

TVS® is registered trademark of HasH



The Power of ONE

www.hashcontrol.com